



Presto-Tap Low Pressure Gauge Products & Accessories

Application:

30# Gauge is used to perform leak tests downstream of 1st stage regulators by connecting quick adapters to Presto-Tap LDS2000RV installed in 1st & 2nd stage regulator taps accessing 1st stage pressure

FIRST STAGE REGULATOR LEAK TESTING 0 - 30# GAUGE PRODUCTS

					N/A		
Part Numbers	Gauge Bleeder	90° Quick Adapter	Straight Quick Adapter	Glycerin Filled Gauge	Dry Gauge	Belt Loop Holster	12" Hose
PT30-LP	X	X		X		X	
PT30-LP-STRAIGHT	X		X	X		X	
PT30-LP-BH90	X	X		X			X
PT30-LP-BH-STRAIGHT	X		X	X			X

Application:

Low pressure gauge used to obtain water column readings and determine regulator lock up, flow and perform low pressure leak tests by reducing lock up pressure to 9" +/- 1/2" wc

LOW PRESSURE LEAK TESTING 0 - 35" WC GAUGE PRODUCTS

							N/A
Part Numbers	Gauge Bleeder	90° Quick Adapter	Straight Quick Adapter	Glycerin Filled Gauge	Dry Gauge	Belt Loop Holster	12" Hose
PT-OZ	X	X		N/A	X	X	
PT-OZ-STRAIGHT	X		X	N/A	X	X	